





Model	<b>RX1270</b>	<b>RX850</b>	<b>RX560</b>	<b>GX560</b>
Change order / delete	<input type="checkbox"/> Delete	<input type="checkbox"/> Move <input type="checkbox"/> Delete	<input type="checkbox"/> Move <input type="checkbox"/> Delete	<input type="checkbox"/> Move <input type="checkbox"/> Delete
Product image	 <p>12MP(Color Monitors) <a href="#">Dimension Drawing</a></p>	 <p>8MP(Color Monitors) <a href="#">Dimension Drawing</a></p>	 <p>5MP(Color Monitors) <a href="#">Dimension Drawing</a></p>	 <p>5MP(Monochrome Monitors) <a href="#">Dimension Drawing</a></p>
Model Variations	RX1270-BK: Anti-Glare coating, with stand, black RX1270-ARBK: Anti-Reflection coating, with stand, black	RX850-BK: Anti-Glare coating, with stand, black RX850-ARBK: Anti-Reflection coating, with stand, black	RX560-BK-MD: Anti-Glare coating, two screens, with dual stand, black RX560-ARBK-MD: Anti-Reflection coating, two screens, with dual stand, black RX560-BK: Anti-Glare coating, one screen, with stand, black RX560-ARBK: Anti-Reflection coating, one screen, with stand, black	GX560-BK-MD: Anti-Glare coating, two screens, with dual stand, black GX560-ARBK-MD: Anti-Reflection coating, two screens, with dual stand, black GX560-BK: Anti-Glare coating, one screen, with stand, black GX560-ARBK: Anti-Reflection coating, one screen, with stand, black
Panel				
Type	Color (IPS)	Color (IPS)	Color (IPS)	Monochrome (IPS)
Backlight	LED	LED	LED	LED
Size	78.4 cm / 30.9"	79 cm / 31.1"	54.1 cm / 21.3"	54.1 cm / 21.3"
Native Resolution	4200 x 2800 (3:2 aspect ratio)	4096 x 2160 (17:9 aspect ratio)	2048 x 2560 (4:5 aspect ratio)	2048 x 2560 (4:5 aspect ratio)
Viewable Image Size (H x V)	652.7 x 435.1 mm	697.9 x 368.0 mm	337.9 x 422.4 mm	337.9 x 422.4 mm
Pixel Pitch	0.1554 x 0.1554 mm	0.1704 x 0.1704 mm	0.165 x 0.165 mm	0.165 x 0.165 mm
Grayscale Tones				10-bit (DisplayPort): 1,024 from a palette of 16,369 (14-bit) tones 8-bit: 256 from a palette of 16,369 (14-bit) tones
Display Colors	10-bit (DisplayPort): 1.07 billion from a palette of 543 billion (13-bit) colors 8-bit: 16.77 million from a palette of 543 billion (13-bit) colors	10-bit (DisplayPort): 1.07 billion from a palette of 68 billion (12-bit) colors 8-bit: 16.77 million from a palette of 68 billion (12-bit) colors	10-bit (DisplayPort): 1.07 billion from a palette of 543 billion (13-bit) colors 8-bit: 16.77 million from a palette of 543 billion (13-bit) colors	
Viewing Angles (H / V, typical)	178° / 178°	178° / 178°	178° / 178°	178° / 178°
Brightness (typical)	1200 cd/m <sup>2</sup>	850 cd/m <sup>2</sup>	1100 cd/m <sup>2</sup>	2500 cd/m <sup>2</sup>
Recommended Brightness for	500 cd/m <sup>2</sup>	500 cd/m <sup>2</sup>	500 cd/m <sup>2</sup>	1000 cd/m <sup>2</sup> , 600 cd/m <sup>2</sup>

Calibration				
Contrast Ratio (typical)	1500:1	1450:1	1500:1	1700:1
Response Time (typical)	12 ms (black-white-black)	20 ms (black-white-black)	12 ms (black-white-black)	12 ms (black-white-black)
<b>Video Signals</b>				
Input Terminals	DisplayPort x 2, HDMI	DisplayPort x 2, DVI-D (dual link) x 2 (two inputs are required)	DisplayPort, DVI-D (dual link)	DisplayPort x 2, DVI-D (dual link)
Output Terminals			DisplayPort (daisy chain)	DisplayPort (daisy chain)
Digital Scanning Frequency (H / V)	31 - 175 kHz / 29 - 61 Hz	31 - 140 kHz / 59 - 61 Hz	31 - 135 kHz / 23 - 61 Hz	31 - 135 kHz / 23 - 61 Hz
<b>USB</b>				
Upstream	USB 2.0: Type-B x 2	USB 2.0: Type-B	USB 2.0: Type-B	USB 2.0: Type-B x 2
Model	<b>RX1270</b>	<b>RX850</b>	<b>RX560</b>	<b>GX560</b>
Downstream	USB 2.0: Type-A x 3	USB 2.0: Type-A x 2	USB 2.0: Type-A x 2	USB 2.0: Type-A x 2
<b>Power</b>				
Power Requirements	AC 100 - 240 V: 50 / 60 Hz	AC 100 - 120 V, 200 - 240 V: 50 / 60 Hz	AC 100 - 240 V: 50 / 60 Hz	AC 100 - 240 V: 50 / 60 Hz
Typical Power Consumption	77 W	111 W	43 W	28 W
Maximum Power Consumption	188 W	227 W	87 W	79 W
Power Save Mode	2 W or less	6 W or less	1 W or less	1 W or less
<b>Sensor</b>	Backlight Sensor, Integrated Front Sensor, Ambient Light Sensor	Backlight Sensor, Integrated Front Sensor, Presence Sensor, Ambient Light Sensor	Backlight Sensor, Integrated Front Sensor, Presence Sensor, Ambient Light Sensor	Backlight Sensor, Integrated Front Sensor, Presence Sensor, Ambient Light Sensor
<b>Features &amp; Functions</b>				
Brightness Stabilization	Yes	Yes	Yes	Yes
Digital Uniformity Equalizer	Yes	Yes	Yes	Yes
Hybrid Gamma PXL	Yes		Yes	
Work-and-Flow	<a href="#">Hide-and-Seek</a> , <a href="#">Switch-and-Go</a> , <a href="#">Point-and-Focus</a>		<a href="#">Point-and-Focus</a>	<a href="#">Switch-and-Go</a> , <a href="#">Point-and-Focus</a>
Preset Modes	CAL Switch (DICOM, CAL1, CAL2, Custom, sRGB, Text)	CAL Switch (DICOM, Custom, CAL1, CAL2, CAL3, Hybrid-γ, sRGB, Text)	CAL Switch (DICOM, CAL1, CAL2, Custom, sRGB, Text)	CAL Switch (DICOM, CAL1, CAL2, Text)
OSD Languages	English, German, French, Italian, Japanese, Simplified Chinese,	English, German, French, Italian, Japanese, Simplified Chinese,	English, German, French, Italian, Japanese, Simplified Chinese,	English, German, French, Italian, Japanese, Simplified Chinese,

	Spanish, Swedish, Traditional Chinese	Spanish, Swedish, Traditional Chinese	Spanish, Swedish, Traditional Chinese	Spanish, Swedish, Traditional Chinese
<b>Physical Specifications</b>				
Net Weight	15.6 kg	22.4 kg (AC adapter included)	RX560-MD, RX560-AR-MD: 17.3 kg  RX560, RX560-AR: 8.1 kg	GX560-MD, GX560-AR-MD: 17.1 kg  GX560, GX560-AR: 8 kg
Net Weight (Without Stand)	11.5 kg	15.8 kg	5.3 kg	5.2 kg
Hole Spacing (VESA Standard)	100 x 100 mm	100 x 100 mm	100 x 100 mm	100 x 100 mm
<b>Certifications &amp; Standards (Please contact EIZO for the latest information.)</b>	CE (Medical Device), EN60601-1, ANSI/AAMI ES60601-1, CSA C22.2 No. 601-1, IEC60601-1, VCCI-B, FCC-B, CAN ICES-3 (B), RCM, RoHS, China RoHS, WEEE, CCC, EAC	CE (Medical Device), EN60601-1, ANSI/AAMI ES60601-1, CSA C22.2 No. 601-1, IEC60601-1, VCCI-B, FCC-B, CAN ICES-3 (B), RCM, RoHS, China RoHS, WEEE, CCC, EAC	RX560, RX560-AR: CE (Medical Device), EN60601-1, ANSI/AAMI ES60601-1, CSA C22.2 No. 601-1, IEC60601-1, VCCI-B, FCC-B, CAN ICES-3 (B), RCM, RoHS, China RoHS, WEEE, CCC, EAC	GX560, GX560-AR: CE (Medical Device), EN60601-1, ANSI/AAMI ES60601-1, CSA C22.2 No. 601-1, IEC60601-1, VCCI-B, FCC-B, CAN ICES-3 (B), RCM, RoHS, China RoHS, WEEE, CCC, EAC
<b>FDA</b>	510(k) Clearance for Breast Tomosynthesis, Mammography, and General Radiography	510(k) Clearance for Breast Tomosynthesis, Mammography, and General Radiography	510(k) Clearance for Breast Tomosynthesis, Mammography, and General Radiography	510(k) Clearance for Breast Tomosynthesis, Mammography, and General Radiography
Model	<b>RX1270</b>	<b>RX850</b>	<b>RX560</b>	<b>GX560</b>
<b>Dedicated Software</b>				
Monitor Quality Control Software RadiCS	Supported	Supported	Supported	Supported
<b>Supplied Accessories (May vary by country. Please contact EIZO for details.)</b>				
Signal Cables	DisplayPort (3 m) x 2, HDMI (2 m)	Dual Link DVI-D (3 m) x 2, DisplayPort (3 m) x 2	RX560-MD, RX560-AR-MD: Dual Link DVI-D (3 m) x 2, DisplayPort (3 m) x 2, DisplayPort (1 m)  RX560, RX560-AR: Dual Link DVI-D (3 m), DisplayPort (3 m)	GX560-MD, GX560-AR-MD: DisplayPort (3 m) x 4, DisplayPort (1 m)  GX560, GX560-AR: DisplayPort (3 m) x 2
Others	AC power cord (3 m), USB Type-A - USB Type-B cable (3 m) x 2, cable cover, Utility Disk (RadiCS LE, PDF installation manual), instructions for use	AC power cord (3 m), AC adapter, USB Type-A - USB Type-B cable (3 m), holder for power cord, Utility Disk (RadiCS LE, ScreenManager Pro for Medical, PDF instructions for use, PDF installation manual), instructions for use	RX560-MD, RX560-AR-MD: AC power cord (3 m) x 2, USB Type-A - USB Type-B cable (3 m) x 2, Utility Disk (RadiCS LE, PDF installation manual), instructions for use  RX560, RX560-AR: AC power cord (3 m), USB Type-A - USB Type-B cable (3 m), Utility Disk (RadiCS LE, PDF installation manual), instructions for use	GX560-MD, GX560-AR-MD: AC power cord (3 m) x 2, USB Type-A - USB Type-B cable (3 m) x 4, Utility Disk (RadiCS LE, PDF installation manual), instructions for use  GX560, GX560-AR: AC power cord (3 m), USB Type-A - USB Type-B cable (3 m) x 2, Utility Disk (RadiCS LE, PDF installation manual), instructions for use
<b>Warranty</b>	Five Years	Five Years	Five Years	Five Years

X Close